

CAS-No.: MSDS

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
:
Product code : 02522

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Laboratory chemicals, Manufacture of substances

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

LOBA CHEMIE PVT.LTD.
107 Wode House Road, Jehangir Villa, Colaba
400005 Mumbai - INDIA
T +91 22 6663 6663 - F +91 22 6663 6699
info@lobachemie.com - www.lobachemie.com

1.4. Emergency telephone number

Emergency number : + 91 22 6663 6663 (9:00am - 6:00 pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, H226
Category 3
Acute toxicity (inhal.), H332
Category 4
Skin corrosion/irritation, H314
Category 1B
Germ cell mutagenicity, H341
Category 2

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

CARBOL FUCHSIN STRONG STAINING SOLUTION

Safety Data Sheet

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS05

GHS07

GHS08

Signal word (CLP) : Danger

Hazard statements (CLP) : H226 - Flammable liquid and vapour.
H314 - Causes severe skin burns and eye damage.
H332 - Harmful if inhaled.
H341 - Suspected of causing genetic defects.

Precautionary statements (CLP) : P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P310 - Immediately call a doctor.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	75 - 99	Not classified
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5	5 - 10	Flam. Liq. 3, H226 Skin Corr. 1A, H314
Phenol	(CAS-No.) 108-95-2 (EC-No.) 203-632-7 (EC Index-No.) 604-001-00-2	1 - 5	Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Oral), H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Muta. 2, H341 STOT RE 2, H373
C.I. Basic Red 9	(CAS-No.) 569-61-9 (EC-No.) 209-321-2 (EC Index-No.) 611-031-00-X	0.01 - 1	Carc. 1B, H350

CARBOL FUCHSIN STRONG STAINING SOLUTION

Safety Data Sheet

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
- First-aid measures after skin contact : Immediately call a POISON CENTER/doctor. Wash with plenty of water/... Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
- First-aid measures after ingestion : Rinse mouth. Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Causes severe skin burns and eye damage. May cause damage to organs.
- Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
- Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water spray.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : No open flames. No smoking. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Use personal protective equipment as required.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Collect spillage. On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

No additional information available

CARBOL FUCHSIN STRONG STAINING SOLUTION

Safety Data Sheet

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with skin and eyes. Do not breathe vapours. Keep away from sources of ignition - No smoking. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep in fireproof place. Keep container tightly closed.
Incompatible materials	: Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Hand protection	: Protective gloves
Eye protection	: Chemical goggles or face shield
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Dark red.
Odour	: No data available
Odour threshold	: No data available
pH	: 4.4
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -114.1 °C
Freezing point	: No data available
Boiling point	: 78.5 °C
Flash point	: 12.78 °C
Critical temperature	: 243 °C

CARBOL FUCHSIN STRONG STAINING SOLUTION

Safety Data Sheet

Auto-ignition temperature	: 363 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable
Vapour pressure	: 2.61 kPa (at 20°C)
Relative vapour density at 20 °C	: 1.59
Relative density	: No data available
Density	: 0.98 g/cm ³
Solubility	: Water: Easily soluble in cold water
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.033 - 0.19 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapours.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Air contact. Direct sunlight. Moisture.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Thermal decomposition generates : Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation: Harmful if inhaled.

ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h

CARBOL FUCHSIN STRONG STAINING SOLUTION

Safety Data Sheet

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 4.4
Serious eye damage/irritation	: Serious eye damage, category 1, implicit pH: 4.4
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Suspected of causing genetic defects.
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Harmful if swallowed. Harmful in contact with skin.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

CARBOL FUCHSIN STRONG STAINING SOLUTION

Safety Data Sheet

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 2924
UN-No. (IMDG)	: 2924
UN-No. (IATA)	: 2924
UN-No. (ADN)	: 2924
UN-No. (RID)	: 2924

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (IATA)	: Flammable liquid, corrosive, n.o.s.
Proper Shipping Name (ADN)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (RID)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Transport document description (ADR)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S., 3 (8), III, (D/E)
Transport document description (IMDG)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S., 3 (8), III
Transport document description (IATA)	: UN 2924 Flammable liquid, corrosive, n.o.s., 3 (8), III
Transport document description (ADN)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S., 3 (8), III
Transport document description (RID)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S., 3 (8), III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3 (8)
Danger labels (ADR)	: 3, 8



IMDG

Transport hazard class(es) (IMDG)	: 3 (8)
Danger labels (IMDG)	: 3, 8



IATA

Transport hazard class(es) (IATA)	: 3 (8)
Hazard labels (IATA)	: 3, 8



ADN

Transport hazard class(es) (ADN)	: 3 (8)
----------------------------------	---------

CARBOL FUCHSIN STRONG STAINING SOLUTION

Safety Data Sheet

Danger labels (ADN) : 3, 8



RID

Transport hazard class(es) (RID) : 3 (8)

Danger labels (RID) : 3, 8



14.4. Packing group

Packing group (ADR) : III

Packing group (IMDG) : III

Packing group (IATA) : III

Packing group (ADN) : III

Packing group (RID) : III

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : FC

Special provisions (ADR) : 274

Limited quantities (ADR) : 5I

Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, R001

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T7

Portable tank and bulk container special provisions (ADR) : TP1, TP28

Tank code (ADR) : L4BN

Vehicle for tank carriage : FL


Transport category (ADR) : 3

Special provisions for carriage - Packages (ADR) : V12

Special provisions for carriage - Operation (ADR) : S2

Hazard identification number (Kemler No.) : 38

Orange plates :



Tunnel restriction code (ADR) : D/E

CARBOL FUCHSIN STRONG STAINING SOLUTION

Safety Data Sheet

EAC code : •3WE
APP code : A(fl)

- Transport by sea

Special provisions (IMDG) : 223, 274
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP1, TP28
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-C
Stowage category (IMDG) : A
Stowage and handling (IMDG) : SW2
Properties and observations (IMDG) : Causes burns to skin, eyes and mucous membranes.
MFAG-No : 132

- Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y342
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 354
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 365
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3, A803
ERG code (IATA) : 3C

- Inland waterway transport

Classification code (ADN) : FC
Special provisions (ADN) : 274
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : FC
Special provisions (RID) : 274
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, R001
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T7
Portable tank and bulk container special provisions (RID) : TP1, TP28
Tank codes for RID tanks (RID) : L4BN
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 38

CARBOL FUCHSIN STRONG STAINING SOLUTION

Safety Data Sheet

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 3, severe hazard to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : C.I. Basic Red 9, Ethanol are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : Ethanol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : Ethanol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Ethanol is listed

Denmark

Class for fire hazard : Class I-1

Store unit : 1 liter

Classification remarks : F <Flam. Liq. 3>; Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

CARBOL FUCHSIN STRONG STAINING SOLUTION

Safety Data Sheet

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product